

H/W Platform	Processor	SunplusDigital Media Processor
Camera	Sensor	CMOS
	Resolution	1292 x 736 pixel
	Light sensitive/Noise	1 Lux / >46 dB
	Waterproof level	IP 69
Recording	Compression / Format	H.264 / MP4
	Frame Rate	30FPS
	Mode	Manual / Continuous looprecording
	Resolution	NTSC (1292x736)
	Time segment	1/3/5 min seamless recording
	Off delay timer	0/1h/2h/4h/6h * Voltage man not lower than 11.2V or system will be off
	Image fileprotection	Set protect onimage files list manually
Display	Resolution	NTSC 30fps / PAL 25fps , 720x480
	Split Windows	2 split window /full screen
	Output	1 RCA A/V Connections
	Screen on/off	Always / ACC on / IR remote controller / double-push Emergency Flashers button (in 1.5sec)/ turn signal / back signal
	View switching	Manual / by turn signal /by backward signal
Playback	Frame Rate	NTSC 30fps / PAL 25fps
	Search	By selectingtime slot
	Operation	Play, Fast Forward, Reverse, Pause, Stop
Storage	Built-in	Total 16GB (including main program)
	Recording Time	2.5hrs HD quality image
	Image file export	USB flash storage
Operation	Setting &Control	IR remote controller
	Power Indicators	Red LED on / off
System Power	On/off	Automatic turn on or off with ACC
	Standby	5/15/30 sec. after ACC off
	Wake-up	vibration detection(default on) or ACC on
	Time	Power Off → On: <4 sec. Power On → off : <1 sec. Standby → Wake up : <4 sec. Wake → Standby : <1 sec.
Language	Multi-Lingual	English, Chinese-Traditional, Chinese-Simplified
Electrical characteristic	Input	Typical Supply Voltage12V Operating Voltage Range 9V ~ 16V
	Power Consumption	Max. 700mA (including system and four cameras)
	Output	5V (camera power)
Temperature	Operation	-40℃~85℃
	Storage	-40℃~85℃
Mechanism	Dimensions	180mm (W) x 130mm (D) x 42mm (H)

規格

硬體系統	處理器	Sunplus 數位影像處理器
鏡頭	Sensor	CMOS
	解析度	1292 x 736 pixel
	照度/噪點	1 Lux / >46 dB
	防水等級	IP 69
錄影	壓縮標準/格式	H.264 / MP4
	幀數	NTSC 30 FPS
	模式	手動 / 自動不間斷
	影片保護	手動 / 自動 (G-Sensor 偵測) 保留 1 分鐘防止覆寫影像檔
	解析度	NTSC 1292x736 像素)
	影片長度	1/3/5 分鐘無縫錄影
	斷電延遲停止	1/2/4/6 小時* (電壓需高於 11.2V, 否則系統將直接關閉)
	防止覆寫	影像檔清單中手動設定
顯示	解析度	NTSC 30fps / PAL 25fps , 720x480
	畫面分割	2 分割 / 全螢幕
	畫面開關	持續顯示 / 電源觸發/ 遙控器開關 / 警示燈 (1.5 秒內連按兩次)/ 方向燈訊號/ 倒車訊號
	輸出	1 RCA A/V 端子連接線
	畫面切換	手動 / 自動偵測方向燈或倒車訊號
播放	解析度	NTSC 30 幀/秒/ PAL 25 幀/秒
	搜尋	檔案清單依時間排序
	操作	前進, 快進, 倒退, 快退, 暫停, 停止
儲存	內建	含作業系統共 16GB
	錄影時間	約 2.5 小時 HD 影像
	檔案匯出	USB 記憶卡/碟
控制	系統設定	紅外線遙控器
	電源指示燈	紅色指示燈
	重置	前面板 RESET 鍵
系統電源	開關	隨汽車電源啟動
	待命	斷電後 5/15/30 秒進入待命模式
	動作時間	Power Off → On: <4 sec. Power On → off: <1 sec. Standby → Wake up: <4 sec. Wake → Standby: <1 sec.
語言	多國	英文, 簡中, 繁中
電氣規格	輸入	支援輸入電壓 12V 工作電壓容許範圍 9V ~ 16V
	功耗	最大 700mA (含主機及 4 個鏡頭)
	輸出	攝影鏡頭: 5V
溫度	工作	-40°C~85°C
	保存	-40°C~85°C
機構	尺寸	180mm (W) x 130mm (D) x 42mm (H)